









Extinguish without any anguish.

Monsher ISI Mark Dry Chemical Powder (Stored Pressure Type) Fire Extinguisher ABC Class

The Monsher ISI Mark ABC Dry Powder (stored pressure type) Fire Extinguisher have been proved effective against all classes of fires like Class A, Class B, Class C as well as electrically started fires. It contains a specialised Mono Ammonium Phosphate (MAP) powder that douses fire speedily and helps deliver safety quickly and effectively. For Class A, B, & C Fires.





TYPE	STORED PRESSURE					
Model. No	MON/EX/ABC/01	MON/EX/ABC/02	MON/EX/ABC/04	MON/EX/ABC/06	MON/EX/ABC/09	
Capacity (Kg)	1	2	4	6	9	
Diameter (mm)	86.5	108	130	150	175	
Height (mm)	340	395	485	550	605	
Empty Weight (Kg)	1.3	1.8	2.8	3.5	4.7	
Filled Weight (Kg)	2.3	3.8	6.8	9.5	13.7	
Operating Temperature	'-20°C TO +55°C					
Working Pressure At 27 C	15 bar					
Maximum Service Pressure	1.8 MPa					
Test Pressure	35 bar					
Average Discharge Time (s)	8	11	15	20	25	
Discharge Range (mts)	< 2	< 2	< 4	< 4	< 4	
Fire Rating	1A, 8B	1A, 13B	2A, 21B	3A, 21B	3A, 55B	

Monsher ISI Mark Dry Chemical Powder (Stored Pressure Type) Fire Extinguisher BC Class

Our ISI Mark Dry Powder (stored pressure type) Fire Extinguisher is ideal for controlling B & C classes of fire caused by liquids like petrol and petroleum products, varnishes, paint, chemical liquids and solvents. It also works well on all gas fires, flammable liquids and electrical fires and fires caused by cooking gas.

For Class B & C fires.

TYPE	STORED PRESSURE				
Model. No	MON/EX/BC/04	MON/EX/BC/06	MON/EX/BC/09		
Capacity (Kg)	4 kg	6 kg	9		
Diameter (mm)	130	150	175		
Height (mm)	485	550	605		
Empty Weight (Kg)	2.8	3.5	4.7		
Filled Weight (Kg)	6.8	9.5	13.7		
Operating Temperature	'-30°C TO +55°C	'-30 [°] C TO +55 [°] C	'-30°C TO +55°C		
Working Pressure At 27 C	15 bar	15 bar	15 bar		
Maximum Service Pressure	1.8 MPa	1.8 MPa	1.8 MPa		
Test Pressure	35 bar	35 bar	35 bar		
Average Discharge Time (s)	15	20	25		
Discharge Range (mts)	< 4	< 4	< 4		
Fire Rating	55 B	89 B	144 B		





Monsher ISI Mark Carbon Dioxide Type Fire Extinguisher

By virtue of being a clean agent, the Monsher ISI Mark CO2 Fire Extinguisher is most effective against Class B and Class C fires. This extinguisher is best suited for providing fire safety to Server rooms, IT rooms, Labs, Food storage and processing areas and more. For Class B & C fires.

TYPE	STORED PRESSURE		ТҮРЕ	MON/CO2/9
Model. No	MON/CO2/2	MON/CO2/4.5	Capacity In Kgs	9
Capacity (Kg)	2	4.5	Diameter (mm)	140
Average discharge time	9 sec	10 sec	Thickness (mm)	4.2
Height	580 mm	705 mm	Hydraulic Test Pressure (bar)	250
Diameter	108 mm	140 mm	Jet Range (m)	2.5
Empty Weight (Kg)	6.2	12.4	Min. Period For Which Jet To Be Maintained (sec)	15
Filled Weight (Kg)	8.2	16.9	Max. Period To Discharge (sec)	36
Operating temperature	'-30°C to +55°C	'-30°C to +55°C	Min. Discharge Quantity (%)	95
Maximum Services	16.9 MPa	16.9 MPa	Height (mm)	1110
Test Pressure	250 bar	250 bar	Empty Weight (kg)	19
Fire Rating	8 B	34 B	Filled Weight (kg)	28
			Working Temperature (C ⁰)	'-30°C to +55°C

